

SUPRESS®

SOUND ENGINEERED FLOOR / CEILING ASSEMBLY

OPEN WEB ENGINEERED WOODEN FLOOR TRUSS 18" DEPTH (ILLUSTRATED IN ELEVATION VIEW)

FINISH FLOOR: RAW

SUBFLOOR: SUPRESS® SOUND-ENGINEERED PLYWOOD™ (SEP) LAYER: SINGLE 3/4" LAYER

STRUCTURAL MEMBER: 18" DEEP OPEN WEB ENGINEERED WOOD FLOOR TRUSS INSTALLED AT 2'-0" O/C SPACING

FRICTION FIT BATT INSULATION TO REACH A DEPTH OF 10" +/- Typically 2 LAYERS OF R-19


SUPRESS® SOUND ISOLATION CHANNEL™ (SIC)

CEILING FINISH: SUPRESS® SOUND-ENGINEERED DRYWALL™ (SED) LAYER: SINGLE 5/8" LAYER,

SOUND TRANSMISSION RATING: STC: 61 minimum

IIC IMPACT RATING: 51 minimum

FIRE RATING: 1 HOUR CLASSIFICATION



SUPRESS®

SOUND - ENGINEERED

Supress Products, LLC

Customer Service 800-456-4061

www.supressproducts.com info@supressproducts.com